## HALLMAN



Type of Gas		Burner	NG	LPG	INPUT (BTU/H)
Natural Gas	LP Gas	Α	1.75	1.18	15000
		В	1.33	0.93	9000
© ©	(B) (A)	С	1.75	1.18	15000
		D	1.33	0.93	9000

Broil	240V, 60Hz,3200W
Oven	240V, 60Hz,2800W
Oven Light	120V,60Hz,25W*2
Oven Fan	120V,60Hz,15W+45W
Max. Power	240V, 60Hz,3310W

	Input Pressure	Output Pressure
NG	7 inch	5 inch
LPG	11 inch	10 inch

Conforms to UL STD. 858 Certified to CSA STD C22.2 NO.61. Conforms to ANSI STD Z21.1-2018 Certified to CSA STD

Minimum distance from the sides of the range above the countertop to flammable walls must be at least 13 inches.

1.1-2018 Household Cooking Gas Appliances.

The minimum horizontal distance is 18 inches between the appliance and flammable structure extending from the cooking surface.

The minimum vertical clearance between the countertop surface and flammable structure above the appliance is 30 inches. The minimum horizontal distance between overhead cabinets installed on either side of the appliance shall not be less than the nominal width of the appliance.

A floor-supported unit requires no space between adjacent flammable structures.

Do not store or use a gasoline liquid propane cylinder or other flammable vapours and liquids in the vicinity if this appliance. The gas appliance pressure regulator must be set for the gas with which the appliance is used with Natural gas. Only the gas

for which the appliance is set shall be identified.

This appliance is shipped from the factory adjusted for use with Natural Gas.

You can find the orifices in the package with LP manual.

Conversion orifices are located in the LP package.

Please follow the instructions in the package with the gas conversion orifices.

Each orifice shall be clearly identified for the gas for which it is designed, and the orifice size shall be indicated on the spud.

Vented unit. See installation instructions.

May be vented. If vented, see installation instructions.

The gas appliance pressure regulator must be set for the gas

with which the appliance is used.

Made In China

S/N: